

Nez Perce County 215 10th Street Lewiston, ID 83501 (208) 799-3100 Fax (208) 799-0349 Latah County 333 E Palouse River Drive Moscow, ID 83843 (208) 882-7506 Fax (208) 882-3494 Clearwater County
105 115th Street
Orofino, ID 83544
(208) 476-7850
Fax (208) 476-7494

Idaho County 903 West Main Grangeville, ID 83530 (208) 983-2842 Fax (208) 983-2845 Lewis County
132 N Hill Street
P O Box 277
Kamiah, ID 83536
(208) 935-2124
Fax (208) 935-0223

FOOD ESTABLISHMENT PLAN REVIEW AND APPROVAL FORM

New	Remode	eled or Altered	Planning & Zoning Approval	Environmental Horner Reviewing Plans Date:	ealth Spec	cialist
	NAN	ΛΕ	ADDRESS	ADDRESS		
Establishment						
Owner/Applicant						
Operator						
Designer/Equipment Supplier						
Plan R	Review F	ee: <mark>\$100</mark> D	ate Fee Paid:	Rece	eipt #:	
Establishment Type: Food Service (605) Retail Market (610) Food Processor (615) Mobile (602) Other: ()			Menu: Full menu to be attached. (Menu changes may require additional equipment.			Risk Category assigned (by EH Staff): Low Medium High
Seating	Capacity	Sq. Footage	No. Employees Per Shift	Date of Opening	Но	urs of Operation

Pre-requisite -

Certified Food Protection Manager (CFPM)

A CFPM is required of at least one employee that has supervisory and or management responsibility and the authority to direct and control food preparation and services. To show proficiency of food safety information is shown by passing a test that is part of an accredited program. There are currently five (5) accredited programs offering the test. They are: Prometric, ServSafe, National Registry Food Safety Professional, 360 training or above training/State Food Safety.

Demonstration of knowledge: Person in Charge (PIC)

Based on the risks inherent to the food operation, during inspections and upon request the PIC shall demonstrate to the inspector knowledge of foodborne disease prevention, application of the hazard analysis and critical control point principles, and the requirements of this code. Demonstrate of knowledge by the PIC may be showed by one (1) of the following: Being a certified food protection manager (CFPM), Completing the Idaho Food Safety Exam, responding correctly to inspector's questions as they relate to specific food operations or complying with the IFC by having no critical violations at time of inspection.

Special processes: Provide a HACCP plan for specialized processing methods such as vacuum packaged food items prepared on-site or otherwise required by the regulatory authority.

Plan Review Process

- A. **Submit plans prior to construction.** Properly prepared plans and specifications for construction, remodeling, or alteration must be submitted to the District Health Department for review and approval. Such plans should include a floor plan of food establishment, plumbing and mechanical plans, and equipment list with make, model and specifications. (Section 8-201.11 and 8-201.12 of the Idaho Food Code, 2004)
- B. **Submit**, if applicable, scale drawing of sewage system, well and water system construction.
- C. APPROVAL of the plans and specifications is required PRIOR to the start of construction/remodel.
- D. **Submit** a *Food Establishment License application* thirty (30) days prior to anticipated opening. The license fee must accompany the application. **(Sec. 8-302.10-14)** (Low risk establishments do not submit fee with application; if the operation is determined to be low risk, it is not required to be licensed nor inspected).
- E. **Preoperational/Final inspection:** The District Health Department must be notified of a request for preoperational inspection prior to the opening of the establishment. The preoperational inspection must verify that the food establishment is constructed and equipped in accordance with the approved plans. **(Sec. 8-203.10)**
- F. **Separate approvals:** Contact the local zoning, building, fire, plumbing and electrical departments for their requirements. If alcoholic beverages are to be sold, contact the Alcohol Beverage Control Bureau (Idaho Department of Law Enforcement) for approval.

Note: After plans are reviewed and approved, applicant must sign final page accepting responsibility and verifying that it is understood that the establishment will be built in accordance with the approved plans.

IDAHO FOOD CODE SECTION BREAKDOWN

Filling out this form: Mark the box under plans if the section is denoted on the plans and applies to the restaurant. Make NA on in the box if the section does not apply to your operations. The final box is used by the EHS when there are modifications made to the plan and reviewed / approved by the EHS.

A - FOOD PROTECTION

FINAL	PLANS	N/A	DESCRIPTION OF CRITERIA AND/OR REQUIREMENTS
			1. Convenient and adequate storage, display, and preparation facilities for ice, frozen food (0-10°F), cold foods (<41°F), hot foods (>135°F), other foods and foods on display. (4-301.11). Type and number of cold holding units: Type and number of hot holding units:
			Adequate dry food storage provided in a clean, dry location, and not located in locker rooms, toilet rooms, dressing rooms, garbage rooms, mechanical rooms, under sewer lines, under open stairwells. (3-305.11 and 12)
			Storage provision to keep all food in non-waterproof containers a minimum of 6"above floor. Bare wood shelving allowed only in dry goods storage area, unopened foods. (3-305.11)
			4. Provision for attached thermometers for all refrigerators, freezers and heat units (4-204.112)
			5. Sneeze guards properly designed on self-serve hot/cold buffets/bars. (Measure 54" to 60" from floor to represent customer mouth height. Guard must block line between mouth and food on display, including end plates) (3-306.11)
			6. Dipper wells provided for ice cream scoops (frozen desserts). (3-304.12(D)

COMMENTS:		

B-FOOD EQUIPMENT AND UTENSILS

L	PLANS	N/A	DESCRIPTION OF CRITERIA AND/OR REQUIREMENTS
			ALL FOOD CONTACT EQUIPMENT must be safe, durable, corrosion-resistant and nonabsorbent; sufficient in weight and thickness to withstand repeated warewashing; finished to be smooth and easily cleanable; resistant to pitting, chipping or distortion; and not allow the migration of deleterious substances or impart colors, odors or tastes to food. (4.101.11)
			Food equipment certified by an ANSI-accredited program meets this standard. (4-205.10)
			All used or existing equipment requires approval prior to installation and be in good repair and capable of being maintained in a sanitary condition. (8-101.10)
			3. Counter-type equipment: movable, on 4"+ legs; or sealed to counter. (4-402.12) Floor-type equipment: movable, on 6"+ legs; or sealed to floor/base. (4-402.12)
			 Space between units or walls closed; or opened sufficient distance for easy cleaning along sides, behind or above. (4-402.11)
			 Aisles - sufficient width: minimum 36"; 42" for two or more workers; wider for mobile equipment. (Uniform Building Code)
			Raw food prep table and food preparation sink provided (if applicable per menu). Prep sinks must be indirectly wasted to sewer. (3-302.11)
			DISH AND UTENSIL WASHING AND SANITIZATION
			7. Adequately sized multi-use utensil and pot wash sinks for manual dishwashing. (4-301.12)
			8. Properly designed drainboards or dish tables provided for soiled and clean utensils. (4-301.13)
			9. Dish machine type: Low temperature, chemical feed □; or High temperature □ Equipped to automatically dispense detergents and sanitizers, with low level alarm. (4-204.117) 1/4" IPS (Iron pipe size) valve for pressure gauge required on the hot water supply line for the hot water sanitizing rinse. (4-204.118)
			10. Warewasher machine(s) provided with a readable data plate indicating the machine operating specifications: Temperature, pressure and conveyor or cycle speed. Machine make; Model number: (4-204.113)
			11. Accurate temperature measuring devices that indicates the temperature of the water in the wash and rinse compartments of warewashing machines. (4-204.115)
			12. If no warewashing sinks or mechanical warewashing machines are provided, then only single-use kitchenware and tableware may be used by food employees and consumers. (4-502.12)
			13. Storage for cleaned equipment, utensils, and single-use and single-service articles shall be in a clean, dry location not exposed to splash or contamination, and 6"+ above floor. (4-903.11)

C - WATER SUPPLIES AND SEWAGE DISPOSAL

FINAL	PLANS	N/A	DESCRIPTION OF CRITERIA AND/OR REQUIREMENTS
			Public water supply (Name of approved supplier/system.)(5-101.11)
			2. Non-municipal supply type: Treatment: PLANS AND SAMPLE MUST BE SUBMITTED AND APPROVED PRIOR TO FINAL INSPECTION. (5-101.11)
			Hot and cold water provided under pressure to all fixtures, and hot water system sufficient to meet the peak hot water demands throughout the food establishment. (5-103.11 - 12)
			4. 140°F water capacity gallons. (5-l03.11 - adequate) Recovery rate:gallons/ºF rise

FINAL	PLANS	N/A	C- WATER SUPPLEIS AND SEWAGE DI DESCRIPTION OF CRITERIA AND/O	
			5. 180°F water and/or booster heater for high temp dish	machines. (4-501.112)
			6. Public sewer - name:	(5-403.11)
			 Septic system or other type disposal. PLANS MUST I PRIOR TO FINAL INSPECTION. (Rules for Subsurfar making equipment, refrigeration equipment and wok ra 	ce Disposal call for AIR COOLED ice
			Grease interceptor or trap sized in accordance to Uniform to be easily accessible for cleaning. (5-402.12)	orm Plumbing Code (UPC), and located

Comments:

D - PLUMBING

Idaho Plumbing Code IDAPA 07.02.06.20, Modifies UPC (2003) "801.2.3 Add: Food Preparation sinks, Pot sinks, Scullery Sinks, dishwashing sinks, silverware sinks, commercial dishwashing machines, silverware washing machines, steam kettles, potato peelers, ice cream dipper wells, and other similar equipment and fixtures must be indirectly connected to the drainage

system by means of an air gap"

FINAL	PLANS	N/A	DESCRIPTION OF CRITERIA AND/OR REQUIREMENTS
			All plumbing of safe materials, sized, installed in accordance with the Uniform Plumbing Code (UPC). (5-201.11, 5-202.11)
			Water flushed walk-in box floor sloped to proper drain. Drain outside walk-in box. Condensate wastes to floor sink or approved hub drain outside walk-ins (UPC 801.2)
			3. Floor sinks must be 50% exposed if under equipment, for cleaning. (UPC 804.1) Floor sinks or drains not enclosed in cabinets - may have unseen flooding, humidity damage. Box out with cabinet base and toe kick. (4-202.17)
			4. Dipper wells: air gap supply line: open (indirect) drain (UPC 801.2.3d)
			5. Dishwasher: air gap fill, vacuum breaker rinse line; open (indirect) drain. (5-402.11) (No direct drain unless in compliance with 5-402.11B)
			6. Food sinks for draining/washing ready-to-serve food: air-gapped indirect drain. (UPC 801.2.3)
			7. Garbage grinder/disposal/drainboard scupper: vacuum breaker supply water (UPC 603)
			8. Ice bin and machine: open (indirect) drain; air gap supply line to reservoir. (UPC 801.2)
			Janitorial faucets/hose bibs/threaded faucets: vacuum breaker required if threaded faucet for hoses. (UPC 603.4.7)
			10. Soap dispensers when located on approved faucets: Approved backflow preventer required (UPC 603)
			11. Soda fountain water line to carbonator: Reduced pressure device required, installed upstream from a carbonating device and downstream from any copper in the water supply line. (5-203.15)(UPC603.4.13) (6 th Edition Cross-Connection Manual)
			12. Hood, self-clean type: Approved backflow protection required. (UPC 603)

BACKFLOW AND BACK SIPHONAGE PROTECTION FOR: (UPC 603.0 and 801.0) Backflow or backsiphonage prevention devices installed on water supply lines shall meet ASSE standards for construction, installation, maintenance and testing for the specific application and type of device. (5-202.14) Air gaps between the water supply inlet and the equipment or fixture shall be twice the diameter of the supply inlet and not less than 1" (5-202.23)

Idaho Plumbing Code IDAPA 07.02.06.19 modifies UPCX (2003) "801.2.3. add Food Preparation sinks, pot sinks, scullery sinks, dishwashing sinks, silverware sinks, commercial dishwashers machines, silverware machines, steam kettles, potatoes peelers, ice cream dippers wells, and other similar equipment and fixtures must be indirectly connected to the drainage system by means of an air gap.

Comments:			

E - TOILET AND HAND-WASHING FACILITIES FOR PATRONS AND EMPLOYEES

FINAL	PLANS	N/A	DESCRIPTION OF CRITERIA AND/OR REQUIREMENTS		
			Patron toilet rooms located so that customers do not pass through food preparation, warewashing or food storage areas. (2-103.11)		
			2. Employee toilet rooms conveniently located and accessible for employee use. (6.402.11)		
			3. Fully enclosed toilet rooms, self-closing doors. (6-202.14)		
			4. Adequate ventilation Window Mechanical (6.304.11)		
			Handwashing lavatory sinks with hot and cold water through mixing faucets. (5-202.12) (15-second water flow required if faucet has automatic shut-off)		
			Adequate number of urinals, water closets and lavatories in toilet rooms. (5-203.12) Female Male		
			7. Waste receptacles provided. (5-501.16) Covered waste receptacles required for disposal of sanitary napkins in toilet rooms used by females. (5-501.17)		
			8. Handwashing cleanser, paper towels, hand dryers or continuous towel rollers provided for handsinks. (6-301.11, 12)		

Comments:			

F - EMPLOYEE HANDWASHING FACILITIES

FINAL	PLANS	N/A	DESCRIPTION OF CRITERIA AND/OR REQUIREMENTS
			 A number of handwashing lavatories necessary for their convenient use shall be provided. (5- 203.11) (Required in food preparation area; dishwashing area; wait stations; restrooms)
			2. Hand cleanser, paper towels, hand dryers or continuous roll towels provided for handsinks.

Comments:

G - GARBAGE AND REFUSE

FINAL	PLANS	N/A	DESCRIPTION OF CRITERIA AND/OR REQUIREMENTS		
			Inside containers adequate, convenient, durable, insect- and rodent-resistant, leakproof and nonabsorbent. (5-501.13) Floor, wall and ceiling in garbage storage areas must be smooth, durable and easily cleanable. (6-101.11)		
			 Outside receptacles for refuse, recyclables and returnables shall be designed to have tight- fitting lids, doors or covers. (5-501.15) Outside garbage area is concrete or asphalt and is smooth, durable and sloped to drain. (5-501.11) 		
			3. At least one mop sink or service sink or curbed cleaning facility equipped with a floor drain shall be provided and conveniently located for cleaning of mops and for the disposal of mop water or similar liquid waste. (5-203.13)		
			4. Mop/broom storage provided, rack or hooks for hanging mops to dry. (6-501.16)		

Comments:

H - VERMIN CONTROL

FINAL	PLANS	N/A	DESCRIPTION OF CRITERIA AND/OR REQUIREMENTS		
			 Outer openings screened (vents, windows) with 16 mesh or smaller screen; outer doors self- closing. (6-202.15) 		
			2. Air screens, plastic curtains provided on doors if needed to control flying insects. (6-202.15)		
			3. Building rodent proof. Wall openings closed. (6-202.15)		

Comments_____

I - STRUCTURAL DESIGN AND MATERIALS

AREA	FLOOR*	BASE**	WALL***	CEILING***		
Dining Area						
Kitchen						
Walk-in Refrigerator and Freezer						
Warewashing Area						
Food Storage Areas						
Toilet Rooms****			4 foot wainscot			
Locker Rooms/Areas						
Mop/Service Area			4 foot wainscot			
Outside Areas (6-102.11) - walking and driving areas surfaced to minimize dust and prevent muddy conditions.						

Comments:			

- *Floors and floor coverings shall be durable sealed concrete, terrazzo, quarry tile, ceramic tile, durable grades of vinyl or plastic tile or tight-fitting wood impregnated with plastic. Floors of nonrefrigerated dry food storage need not be sealed. Carpet may not be used in food preparation or processing areas, walk-in refrigerators, warewashing areas, refuse storage rooms and toilet rooms where handwashing lavatories, urinals and toilets are located. (6-101.11)
- **Base junctures between walls and floors shall be coved and constructed so that no seam will be open more than 1/32 inch. Where water-flush cleaning methods, the floor shall be graded to a drain, coved and sealed. (6-201.13)
- ***Walls, wall coverings and ceilings shall be nonabsorbent, finished and sealed to be easily cleanable and light colored in food preparation and processing areas, food storage areas, warewashing areas, walk-in refrigerators, dining areas, food display areas, retail sales areas, food service areas, dressing rooms, locker rooms, toilet rooms, servicing areas, and refuse storage rooms. Walls and ceilings of nonrefrigerated dry food storage areas and rooms need not be finished and sealed; ceiling studs, rafters may be exposed and rough-surfaced materials used in dining areas. Acoustical materials shall not be used in food preparation and processing rooms, warewashing rooms and refuse storage rooms. (6-201.11)
- ****Floors and walls in restrooms shall be smooth, hard, nonabsorbent surfaces such as Portland cement, concrete, ceramic tile or other approved material. Floor material must extend upward onto the walls at least 5 inches. Walls shall be of said materials not adversely affected by moisture. Bars, paper dispensers, soap holders that are provided on or within walls shall be installed and sealed to protect structural elements from moisture. (Uniform Building Code, 807.1 & 2)

J - LIGHTING, Artificial/Natural

			o Elomino, / limbia/Natarai		
FINAL	PLANS	N/A	DESCRIPTION OF CRITERIA AND/OR REQUIREMENTS		
			All surfaces where food employees are working with food or with utensils such as knives, slicers, grinders or saws - 50 ft. Candles (6-303.11)		
			2. At surfaces where food is provided for consumer self-service such as buffets and salad bars, and at handwashing, warewashing, equipment/utensil storage areas and toilet rooms – 20 ft. candles (6-303.11)		
			3. All other areas, 30" from floor - 10 ft. Candles (6-303.11i)		
			4. Light shielding provided in all food handling, warewashing, open food storage, utensil storage and single service storage areas. (6-202.11)		
			5. Lights in hoods UL approved. (National Fire Protection Association)		
0 1	·				

			2.	At surfaces where food is provided for consumer self-service such as buffets and salad bars, and at handwashing, warewashing, equipment/utensil storage areas and toilet rooms – 20 ft. candles (6-303.11)
			3.	All other areas, 30" from floor - 10 ft. Candles (6-303.11i)
			4.	Light shielding provided in all food handling, warewashing, open food storage, utensil storage and single service storage areas. (6-202.11)
			5.	Lights in hoods UL approved. (National Fire Protection Association)
Comments:		•	•	
Johnnents.	·			
				K - VENTILATION
FINAL	PLANS	N/A		DESCRIPTION OF CRITERIA AND/OR REQUIREMENTS
			1.	Sufficient ventilation to all rooms to keep them free of excessive heat, steam, grease, vapors, condensation, obnoxious odors and fumes which are a result of the food operation. (6-304.11) Commercial kitchen hoods shall be designed, constructed and installed according to the Uniform Mechanical and Building Codes. (UMC Section 507 and 508)
			2.	Type of hood: Type I (Grease filters/fire suppression Type II (No grease produced) Wall hung Island Back-shelf ventilator Self-cleaning
				Drawings provided: elevated drawing of hood and duct system floor plan showing hood, make-up air registers, equipment
			3.	Hood construction: 22 gage-Type I, 24 gage-Type II. Welded joints & seams. (UMC 508.2) Six-inch overhang extending beyond cooking equipment. Hood exhaust outlets terminating two feet above roof, ten feet from any air intake openings. (UMC 507.11)
			4.	Restrooms vented, or with openable, screened windows (to keep them free of objectionable odors). (6-304.11)
20.000000000000000000000000000000000000		<u> </u>		
Comments:				
FINAL	PLANS	N/A		L - OTHER OPERATIONS DESCRIPTION OF CRITERIA AND/OR REQUIREMENTS
			1.	Dressing rooms or areas provided if employees change their clothes in the establishment. Lockers provided for storage of employees possessions. (6-305.11)
			2.	Cleaning materials/pesticides are not stored near food, food contact equipment or containers, paper products. Separate storage, closed cabinets for pesticides. (7-201.11)
			3.	A private home, a room used as living or sleeping quarters, or an area directly opening into a room used as living or sleeping quarters may not be used for conducting food establishment operations. (6-202.111) Living or sleeping quarters located on the premises of a food establishment shall be separated from rooms and areas used for food establishment operation by complete partitioning and solid self-closing doors. (6-202.111 and 112)
			4.	Laundry equipment (washer/dryer) not located in area with exposed food, clean equipment, utensils, or unwrapped single-service and single-use articles (4-401.11.C)
			5.	Utility service lines and pipes not installed on the floors, nor unnecessarily exposed on walls or ceilings; those that are exposed shall not obstruct or prevent cleaning of the floors, walls or

ceilings. (6-201.12)

Comments:	

APPROVAL of the plans and specifications does not constitute endorsement or acceptance of the completed establishment, structure or equipment installation. Any changes or deviations from these approved plans must be submitted in writing and approved by the department.

IF NOT OTHERWISE MENTIONED, THE RULES IN IDAPA 16.02.19 "FOOD SAFETY AND SANITATION STANDARDS FOR FOOD ESTABLISHMENTS (IDAHO FOOD CODE) SHALL APPLY.

I understand and agree to comply with the above listed requirements of the Idaho Food Code and accept responsibility for any changes needed when not in compliance.

Key to Abbreviations:

NFPA - National Fire Protection Association IDAPA - Idaho Administrative Procedures Act ASSE - American Society of Safety Engineers ANSI - American National Standards Institute UBC - Uniform Building Code UMC - Uniform Mechanical Code UPC - Uniform Plumbing Code UL - Underwriters' Laboratories